

ICM-24

Chassis TFT-Monitor 24"



overview:

- TFT / LCD monitor chassis
- screen diagonal 24"
- Interface RGB analog / DVI
- optional HDMI / DP
- mounting via VESA 100
- longterm availability
- customizations possible

Description:

The ICM-24 chassis monitors are specifically designed for use in industrial environments. The monitors can be mounted on support arms or similar fixtures using a VESA mount. With a stand, they can also be used as desktop monitors. The robust housing allows for operation even in the harshest environments, including 24-hour continuous use. The standard models feature both an analog VGA input and a DVI input.

technical data:

overview:

24" industrial TFT / LCD monitor chassis for support arms or desktop monitor

Resolution:

max. 1920x1080

Brightness:

min. 250cd/qm

Contrast:

1000:1

Interface:

VGA DVI, optional HDMI / DP

Adjustments:

via On Screen Menü

MTBF:

Backlights min. 35000h

controls:

Touchscreen (Option)

power supply

90/260 VAC internal

mechanical dimensions:

case: about 582 x 350 x 62 mm

material:

case: steel

environmental conditions:

operating: 0-50°C

storage 0-65°C

humidity: 10 - 80 % rel. humidity

not condensing

norms:

EMV: EN55022 EN55024 EN61010-1

part number:

10050608	ICM-24-24" Chassis-Monitor
10050614	ICM-24T-24" Chassis-Monitor with touchscreen
10050528	Option protected glass ICM-24
10050519	Option HDMI / Displayport
10050535	Option High brightness
10050532	option 9-36 VDC

ICM-24

Chassis TFT-Monitor 24"

