

IOM-06

TFT-monitor 6,4" openframe



Overview

- TFT / LCD monitor as openframe modul
- Screen diagonal 6,5"
- Connector RGB analog / DVI
- Optional video input
- Mounting via flanges
- Long term available
- Customization possible

Description

The openframe monitors of the IOM series are specially suitable for industrial use. The monitors can be integrated with existing front panels or control panels. The robust case enables use in the toughest environments in 24-hour operation. The standard units have an external wide range power supply, an analog VGA / DVI-D input. At the back of the monitor can be mounted on a VESA holder, or via the existing mounting plates can be integrated.

Technical data

Overview:

Industrial TFT monitor as openframe modul for control panel or control desk

Interfaces:

HD-SUB15 analog RGB, DVI-D
optional video input

Resolution:

max. 640x480

Adjustments:

via on-screen-menu

Brightness:

min. 400 cd/qm

Contrast:

600:1

Power supply:

12VDC, 100-240VAC via external Power supply

Mechanical dimension:

Case: about 176 x 130 x 49mm

Material:

Case: Steel

Ambient conditions:

Operating temperature 0-50°C

Storage temperature 0-65°C

Humidity: 10 - 80 % rel. humidity, not condensing

Norms

EN55022 EN55024 EN61010-1

Part number

10050368 IOM-06 6,5" openframe monitor

IOM-06

TFT-monitor 6,5" Openframe

