

IOM-15-2

TFT-Monitor 15" Openframe Modul



overview:

- TFT / LCD monitor Openframe Modul
- screen diagonal 15"
- Interface RGB analog and DVI
- mounting via brackets
- 12VDC via external power adapter
- on-screen-menu
- customizations possible

Description:

The IOM-15-2 open-frame monitors are designed for use in industrial applications. They can be easily integrated into existing front panels or control consoles. The robust steel sheet housing with integrated control electronics and power supply enables reliable operation even in harsh environments and supports 24/7 continuous operation. Standard units are equipped with VGA and DVI inputs.

technical data:

overview:

15" industrial TFT / LCD monitor Openframe-Modul for control panels and control desks

Resolution:

max. 1024x768

Brightness:

min. 400cd/qm

Contrast:

500:1

Interface:

VGA , DVI

Adjustments:

via On Screen Menü

MTBF:

Backlights min. 35000h

power supply

12VDC via external power adapter

mechanical dimensions:

case with brackets: about 348 x 255 x 40mm

material:

case: steel

environmental conditions:

operating: 0-50°C

storage 0-65°C

humidity: 10 - 80 % rel. humidity

not condensing

norms:

EMV: EN55022 EN55024 EN61010-1

part number:

100504339 IOM-15-2 15" Openframe-Monitor 12VDC

IOM-15-2

TFT-Monitor 15" Openframe Modul

