

IOM-42

TFT-Monitor 42" Openframe Modul



overview:

- TFT / LCD monitor Openframe Modul
- screen diagonal 42"
- Interface RGB analog / DVI
- optional HDMI / DP
- mounting via brackets
- longterm availability
- customizations possible

Description:

The Openframe monitors IOM-42 are specifically designed for use in industrial environments. The monitors can be integrated into existing front panels or control consoles using the mounting brackets. The robust housing allows operation even in the harshest environments in 24-hour continuous use. The standard units feature an external wide-range power supply and an analog VGA / DVI input. On the rear side, the monitor can be mounted using a VESA mount.

technical data:

overview:

42" industrial TFT / LCD monitor Openframe-Modul for control panels and control desks

Resolution:

max. 1920x1080

Brightness:

min. 350cd/qm

Contrast:

3000:1

Interface:

VGA DVI, optional HDMI / DP

Adjustments:

via On Screen Menü

MTBF:

Backlights min. 35000h

controls:

Touchscreen (Option)

power supply

115/230 VAC internal

mechanical dimensions:

case with brackets: about 1020 x 647 x 164mm

material:

case: steel

environmental conditions:

operating: 0-50°C

storage 0-65°C

humidity: 10 - 80 % rel. humidity

not condensing

norms:

EMV: EN55022 EN55024 EN61010-1

part number:

10050372 IOM-42 42" Openframe-Monitor

10050511 option 24VDC

10050516 option 12VDC

IOM-42

TFT-Monitor 42" Openframe Modul

