

IPM-15-T

Panelmonitor 15"



overview:

- TFT / LCD touchscreen monitor
- screen diagonal 15"
- Interface RGB analog / DVI and HDMI
- wideangledisplay 178°
- frontpanel powder coated black RAL 9005 with threaded bolts
- touchscreen 5-wire resistive, USB

Description:

The industrial panelmonitors of the IPM series are specifically suitable for use in control panels, control desk and control cabinet doors. Mounting on rear side with threaded bolts in the front panel, so a flat front is maintained. The robust Housing enables the use in the toughest environments with 24-hour operation. The devices are equipped with 24VDC power supply, VGA, DVI and HDMI input as well as an 5-wire resistive touchscreen. Standard units are equipped with a 9–36 VDC wide-range power supply.

technical data:

overview:

15" industrial TFT / LCD monitor for mounting in control panels and control desks

Resolution:

max. 1024x768

Brightness:

min. 350cd/qm

Contrast:

1000:1

Interface:

VGA, DVI, HDMI

Adjustments:

via On Screen Menü

MTBF:

Backlights min. 35000h

controls:

touchscreen 5-wire resistive, USB

power supply

9-36 VDC via internal power supply / converter

mechanical dimensions:

case: 345 x 292 x 58 mm

frontpanel: 428 x 336 x 4 mm

material:

frontpanel: aluminium powder coated, black RAL9005

environmental conditions:

operating: 0-50°C

storage 0-65°C

humidity: 10 - 80 % rel. humidity

not condensing

norms:

EMV: EN55022 EN55024 EN61010-1

part number:

10050421 IPM-15T Panelmonitor 24 VDC